

## Product Data Sheet

**Product Code:     MTPCSD**

Product Description:     85/15% polyester cotton satin Work wear

TEST	SPECIFICATION	TEST METHOD
Base Fabric	85/15% poly cotton wp satin	ISO 1833
Construction	205filx10s 65/35% 108x60	ISO 7211/2
Coating	N/A	
Finish	Pure Finish	
Fabric Weight	275 g/m <sup>2</sup>	ISO 3801
Coated Weight	N/A	ISO 3801
Total Weight	N/A	ISO 3801
Useable Width	160cms	EN 1773
Chromaticity to EN2041	YES	EN20471
Spray Rating	N/A	ISO 4920
Tensile Strength Warp (N)	1200N	ISO 13934-1
Tensile Strength Weft (N)	900N	ISO 13934-1
Tear Strength Warp (N)	55N	ISO 4674
Tear Strength Weft (N)	45N	ISO 4674
Colour Fastness to light	4	ISO 105
Colour Fastness to Water	4	ISO 105 E01
Colour Fastness perspiration acid	4	ISO 105 E04
Colour Fastness perspiration alkaline	4	ISO 105 E04
Colour Fastness to Washing 40c	4	ISO 105 C06
Fastness to Rubbing Wet Dry	4	ISO 105 x12
Dimensional Stability	2%	ISO 6330
Pilling Resistance	3-4	ISO 12045.1.2000
Abrasion Resistance	80000	ISO 12947-2-2000
Water Vapour Resistance Ret	N/A	ISO 11092
Resistance to Water Penetration	N/A	ISO 20811

**DISCLAIMER** The information contained in the product Data Sheet is based on results obtained on the sample assessed at the time in accordance with the method provided. The values are a guide to purchasers of the Fabric to evaluate the Fabric and determine its suitability for their products intended end use.

Product Code:MTPCSD

**WASHING INSTRUCTION**



- 1.Hot machine wash 60C
- 2.No Bleach or colour additives
- 3.Tumble dry normal medium heat
- 4.Regular ironing steam or dry

**ADDRESS:** TEXCHANNEL IMP. & EXP. CO., LTD.  
ROOM 2302A,BANK CENTER ,NO.189 XIAHE ROAD,XIAMEN 361003 P.R. CHINA

**SIGNED:**



**DISCLAIMER:** The information contained in the product Data Sheet is based on results obtained on the sample assessed at the time in accordance with the method provided. The values are a guide to purchasers of the Fabric to evaluate the Fabric and determine its suitability for their products intended end use.